



(19)

(11) Publication number:

**61120433 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **59241942**(51) Intl. Cl.: **H01L 21/58**(22) Application date: **16.11.84**

(30) Priority:

(43) Date of application  
publication: **07.06.86**(84) Designated contracting  
states:(71) Applicant: **TOSHIBA CORP**(72) Inventor: **KAGINO MINORU**

(74) Representative:

**(54) DIE BONDING DEVICE**

(57) Abstract:

**PURPOSE:** To simplify the wafer handling operation between electrical testing and die bonding processes, by providing a device which can read out chip position information and quality characteristics information stored in a memory medium while recognizing the correspondence of the information with the wafer on which the information is concerned.

**CONSTITUTION:** Information on electric tests of each wafer is stored together with identification information as information 10a, 11a... in a memory medium 1 such as a floppy disk or the like. A wafer is taken out from a magazine 2 and identification information 9 marked on the wafer 7 or identification information 8 marked on a jig 6 is read out by an identification information reading out section 4. According to the identification information thus read, the information having the same

identification information is selected from the memory medium 1 by a data selecting section 5 and read out. A die bonding section 3 is caused to operate according to this information. This construction can thus eliminate any possibility of becoming impossible to check the wafer even if the order of wafers is changed.

COPYRIGHT: (C)1986,JPO&Japio

